

**CLAIMS**

What is claimed is:

1. An attachment system for a modular component of an electronic device,  
comprising:  
5 a latch member configured for securing the modular component to the electronic  
device; and  
a flexible release member movably coupled to the latch member, wherein the  
flexible release member comprises a grip configured for bending the flexible  
release member to effectuate a movement of the mechanical latch to a  
10 released position.
2. The attachment system of claim 1, wherein the latch member comprises a  
flexible portion that is inwardly bendable with bending of the flexible release member.
- 15 3. The attachment system of claim 2, wherein the latch member comprises a  
fixed end and a free end adjacent the flexible portion.
4. The attachment system of claim 3, wherein the latch member is configured  
for lateral mounting to the modular component.

20

5. The attachment system of claim 4, wherein the flexible release member is configured for mounting to an accessible side of the modular component.

6. The attachment system of claim 5, wherein the flexible release member is rotatably coupled to the latch member.

7. The attachment system of claim 1, wherein the latch member and the flexible release member each comprise a fixed end configured for coupling to adjacent sides of the modular component.

10

8. The attachment system of claim 7, wherein the latch member and the flexible release member are rotatably coupled at opposite ends from the fixed ends.

9. The attachment system of claim 1, wherein the flexible release member is bowable to a substantially curved geometry at the released position.

10. A modular component for a computer system, comprising:  
a modular housing comprising an accessible side and a lateral side;  
a low profile latch coupled to the lateral side; and  
a flexible and graspable release member coupled to the accessible side and movably coupled to the low profile latch.

11. The modular component of claim 10, wherein the modular housing  
comprises a cooling device.

12. The modular component of claim 10, wherein the modular housing  
5 comprises a memory device.

13. The modular component of claim 10, wherein the modular housing  
comprises electronic circuitry.

10 14. The modular component of claim 13, wherein the electronic circuitry  
comprises an electrical plug movably coupled to the modular housing.

15 15. The modular component of claim 10, wherein the flexible and graspable  
release member is outwardly bowable.

16. The modular component of claim 15, wherein the low profile latch is  
inwardly releasable with bowing of the flexible and graspable release member.

17. A method of forming a tool-free connector for modular computing  
20 components, comprising:  
providing a first flexible member having a latch;

providing a second flexible member having a finger grip; and  
rotatably coupling free ends of the first and second flexible members to facilitate  
release of the latch.

5           18.     The method of claim 17, wherein providing the first flexible member having  
the latch comprises forming a laterally activated latch mechanism.

19.     The method of claim 18, wherein providing the second flexible member  
having the finger grip comprises forming an outwardly bendable latch release mechanism.

10

20.     The method of claim 17, wherein rotatably coupling free ends comprises  
facilitating lateral movement of the free ends in response to bending of the second  
flexible member.